

## Autogas (nach EN 589)

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **Autogas (nach EN 589)**  
Registration number (REACH) Not relevant (mixture)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Propellant  
Brennstoff

#### 1.3 Details of the supplier of the safety data sheet

SCHARR CPC GmbH  
Hentrichstraße 65  
47809 Krefeld  
Germany

Telephone: +49 2151 5219-0  
Telefax: +49 2151 5219-22  
e-mail: info@scharr-cpc.de  
Website: www.scharr-cpc.de

e-mail (competent person) produktsicherheit@scharr-cpc.de

#### 1.4 Emergency telephone number

Poison centre			
Country	Name	Postal code/city	Telephone
Germany	Giftinformation Freiburg	79106 Freiburg im Breisgau	+49 (0)761 19240

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Hazard class	Category	Hazard class and category	Hazard statement
flammable gas	1A	Flam. Gas 1A	H220
gas under pressure	L	Press. Gas L	H280
hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Contains gas under pressure; may explode if heated. Spillage and fire water can cause pollution of watercourses.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- signal word danger
- pictograms

## Autogas (nach EN 589)

Version number: 2.0  
 Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

GHS02, GHS04



**- hazard statements**

H220 Extremely flammable gas.  
 H280 Contains gas under pressure; may explode if heated.  
 H412 Harmful to aquatic life with long lasting effects.

**- precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P273 Avoid release to the environment.  
 P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
 P381 In case of leakage, eliminate all ignition sources.  
 P410+P403 Protect from sunlight. Store in a well-ventilated place.  
 P501 Dispose of contents/container to industrial combustion plant.

**- supplemental hazard information**

EUH066 Repeated exposure may cause skin dryness or cracking.

### 2.3 Other hazards

of no significance

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures













Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
propane	CAS No 74-98-6  EC No 200-827-9  Index No 601-003-00-5  REACH Reg. No 01-2119486944-21-xxxx	≤ 95	Flam. Gas 1A / H220 Press. Gas C / H280	
butane	CAS No 106-97-8  EC No 203-448-7  Index No 601-004-00-0  REACH Reg. No 01-2119474691-32-xxxx	≤ 80	Flam. Gas 1A / H220 Press. Gas L / H280	

**Autogas (nach EN 589)**

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
isobutane	CAS No 75-28-5  EC No 200-857-2  Index No 601-004-00-0  REACH Reg. No 01-2119485395-27- xxxx	≤ 80	Flam. Gas 1A / H220 Press. Gas L / H280 Aquatic Chronic 3 / H412	 
propene	CAS No 115-07-1  EC No 204-062-1  Index No 601-011-00-9  REACH Reg. No 01-2119447103-50- xxxx 01-2119860639-24- xxxx	≤ 10	Flam. Gas 1A / H220 Press. Gas L / H280	 
but-1-ene		≤ 10	Flam. Gas 1A / H220 Press. Gas C / H280	 
ethane	CAS No 74-84-0  EC No 200-814-8  Index No 601-002-00-X  REACH Reg. No 01-2119486765-21- xxxx	≤ 5	Flam. Gas 1A / H220 Press. Gas L / H280	 
isopentane	CAS No 78-78-4  EC No 201-142-8  Index No 601-085-00-2  REACH Reg. No 01-2119475602-38- xxxx	≤ 4	Flam. Liq. 1 / H224 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	   

For full text of abbreviations: see SECTION 16.

**Autogas (nach EN 589)**

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

**SECTION 4: First aid measures****4.1 Description of first aid measures****General notes**

Do not leave affected person unattended. Remove victim out of the danger area. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Self-protection of the first aider.

**Following inhalation**

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

**Following skin contact**

Thaw frosted parts with lukewarm water. Do not rub affected area.

**Following eye contact**

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

**Following ingestion**

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

Breathing difficulties. Frostbite. Headache. Vertigo.

**4.3 Indication of any immediate medical attention and special treatment needed**

Subsequent observance for pneumonia and pulmonary oedema. Supervise the blood circulation.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing media**

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO<sub>2</sub>)

**Unsuitable extinguishing media**

Water jet

**5.2 Special hazards arising from the substance or mixture**

Contact with the product can cause burns and/or frostbite. Contains gas under pressure; may explode if heated. Danger of bursting container.

**Hazardous combustion products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

**5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

**Autogas (nach EN 589)**

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

Remove persons to safety. Ventilate affected area. Avoidance of ignition sources.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Provision of sufficient ventilation.

**6.2 Environmental precautions**

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

**6.3 Methods and material for containment and cleaning up**

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

**6.4 Reference to other sections**

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

**7.2 Conditions for safe storage, including any incompatibilities**

Managing of associated risks

- flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Lagerklasse (storage class according to TRGS 510, 2 A (gases (except aerosol dispensers and light-ers))  
Germany)

- packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

## Autogas (nach EN 589)

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)								
Country	Name of substance	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Source
AT	butane	106-97-8	MAK	800	1.900			GKV
AT	propene	115-07-1	MAK	200		400 (30 min)		GKV
AT	propane	74-98-6	MAK	1.000	1.800			GKV
AT	isobutane	75-28-5	MAK	800	1.900			GKV
AT	iso-pentane	78-78-4	MAK	600	1.800			GKV
CH	butane	106-97-8	MAK	800	1.900	3.200	7.600	SUVA
CH	propene	115-07-1	MAK	10.000	17.500			SUVA
CH	ethane	74-84-0	MAK	10.000	12.500			SUVA
CH	propane	74-98-6	MAK	1.000	1.800	4.000	7.200	SUVA
CH	isobutane	75-28-5	MAK	800	1.900	3.200	7.600	SUVA
CH	iso-pentane	78-78-4	MAK	600	1.800	1.200	3.600	SUVA
DE	butane	106-97-8	AGW	1.000	2.400	4.000	9.600	TRGS 900
DE	propane	74-98-6	AGW	1.000	1.800	4.000	7.200	TRGS 900
DE	isobutane	75-28-5	AGW	1.000	2.400	4.000	9.600	TRGS 900
DE	iso-pentane	78-78-4	AGW	1.000	3.000	2.000	6.000	TRGS 900
DE	iso-pentane	78-78-4	MAK	1.000	3.000	2.000	6.000	DFG
EU	iso-pentane	78-78-4	IOELV	1.000	3.000			2006/15/EC

#### Notation

STEL

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours  
time-weighted average (unless otherwise specified)

#### Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
but-1-ene		DNEL	769 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
but-1-ene		DNEL	1.530 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects

## Autogas (nach EN 589)

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

Relevant DNELs of components of the mixture						
Name of sub-stance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
isopentane	78-78-4	DNEL	3.000 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
isopentane	78-78-4	DNEL	432 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- hand protection

Wear protective gloves.

- type of material

PE: polyethylene, CR: chloroprene (chlorobutadiene) rubber, IIR: isobutene-isoprene (butyl) rubber

- material thickness

> 0,35 mm

- breakthrough times of the glove material

0,4 mm

>120 minutes (permeation: level 4)

- other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

[In case of inadequate ventilation] wear respiratory protection. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	gaseous (liquefied)
Colour	colourless
Odour	characteristic - disagreeable - nach Odoriermittel
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	-42 – -0,5 °C at 1.013 hPa

## Autogas (nach EN 589)

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

Evaporation rate	not determined
Flammability	flammable gas in accordance with GHS criteria
Lower and upper explosion limit	1,4 vol% - 10 vol%
Flash point	-87 – -82 °C at 1.013 hPa
Auto-ignition temperature	365 – 460 °C
pH (value)	not determined

### Solubility(ies)

Water solubility	24,4 mg/l at 25 °C
------------------	--------------------

### Partition coefficient

Partition coefficient n-octanol/water (log value)	1,81 (pH value: 7, 20 °C)
---------------------------------------------------	---------------------------

Vapour pressure	2.200 – 7.200 hPa at 20 °C
-----------------	----------------------------

### Density and/or relative density

Density	0,5 – 0,58 g/cm <sup>3</sup> at 20 °C
---------	---------------------------------------

Particle characteristics	not relevant (gaseous)
--------------------------	------------------------

## 9.2 Other information

Information with regard to physical hazard classes

Flammable gases

- explosion limits	1,4 vol% - 10 vol%
--------------------	--------------------

Other safety characteristics

Solid content	0 %
Temperature class (EU, acc. to ATEX)	T2 (maximum permissible surface temperature on the equipment: 300°C)



## Autogas (nach EN 589)

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Gas under pressure. Risk of ignition.

If heated:

Danger of explosion, Gas under pressure, Danger of bursting container

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### 10.5 Incompatible materials

Oxidisers

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
isopentane	78-78-4	oral	LD50	>2.000 mg/kg	rat
isopentane	78-78-4	inhalation: vapour	LC50	>25,3 mg/l/4h	rat

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

## Autogas (nach EN 589)

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

### Other information

Repeated exposure may cause skin dryness or cracking.

## 11.2 Information on other hazards

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Acc. to 1272/2008/EC: Harmful to aquatic life with long lasting effects.  
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 1, slightly hazardous to water (Germany)

Aquatic toxicity (acute)			
Endpoint	Value	Species	Exposure time
LC50	91,42 mg/l	fish	96 h
EC50	11,89 mg/l	algae	96 h

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
propane	74-98-6	LC50	49,9 mg/l	fish	96 h
propane	74-98-6	EC50	19,37 mg/l	algae	96 h
butane	106-97-8	LC50	49,9 mg/l	fish	96 h
butane	106-97-8	EC50	19,37 mg/l	algae	96 h
isobutane	75-28-5	LC50	49,9 mg/l	fish	96 h
isobutane	75-28-5	EC50	19,37 mg/l	algae	96 h
but-1-ene		LC50	19 mg/l	fish	96 h
but-1-ene		EC50	6,5 mg/l	algae	96 h
propene	115-07-1	LC50	51,7 mg/l	fish	96 h
propene	115-07-1	EC50	12,1 mg/l	algae	96 h
isopentane	78-78-4	EC50	5,2 mg/l	algae	96 h
isopentane	78-78-4	LC50	12,8 mg/l	fish	96 h

## Autogas (nach EN 589)

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
isopentane	78-78-4	LL50	34,05 mg/l	fish	96 h
isopentane	78-78-4	EL50	59,44 mg/l	aquatic invertebrates	48 h
ethane	74-84-0	LC50	49,9 mg/l	fish	96 h
ethane	74-84-0	EC50	19,37 mg/l	algae	96 h

### Biodegradation

Data are not available.

## 12.2 Persistence and degradability

### Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
isopentane	78-78-4	oxygen depletion	71,43 %	28 d		ECHA

## 12.3 Bioaccumulative potential

Data are not available.

### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
propane	74-98-6		1,09 (pH value: 7, 20 °C)	
butane	106-97-8		1,09 (pH value: 7, 20 °C)	
but-1-ene			2,4	
propene	115-07-1		1,77 (pH value: 7, 20 °C)	
isopentane	78-78-4		4 (pH value: 6,6, 25 °C)	
ethane	74-84-0		1,09 (pH value: 7, 20 °C)	

## 12.4 Mobility in soil

Data are not available.

## 12.5 Results of PBT and vPvB assessment

Data are not available.

## 12.6 Endocrine disrupting properties

None of the ingredients are listed.

## 12.7 Other adverse effects

Data are not available.

## Autogas (nach EN 589)

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagegings

It is a dangerous waste; only packagegings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR/RID/ADN	UN 1965
IMDG-Code	UN 1965
ICAO-TI	UN 1965

#### 14.2 UN proper shipping name

ADR/RID/ADN	HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S.
IMDG-Code	HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S.
ICAO-TI	Hydrocarbon gas mixture, liquefied, n.o.s.
Technical name (Hazardous ingredients)	Propan oder Gemisch A, B oder C

#### 14.3 Transport hazard class(es)

ADR/RID/ADN	2 (2.1)
IMDG-Code	2.1
ICAO-TI	2.1

#### 14.4 Packing group

not assigned

#### 14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

#### 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

#### 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

#### Information for each of the UN Model Regulations

## Autogas (nach EN 589)

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

### Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - additional information

Classification code 2F  
Danger label(s) 2.1



Special provisions (SP) 274, 583, 652(ADR), 660, 662  
Excepted quantities (EQ) E0  
Limited quantities (LQ) 0  
Transport category (TC) 2  
Tunnel restriction code (TRC) B/D  
Hazard identification No 23

### International Maritime Dangerous Goods Code (IMDG) - additional information

Marine pollutant -  
Danger label(s) 2.1



Special provisions (SP) 274  
Excepted quantities (EQ) E0  
Limited quantities (LQ) 0  
EmS F-D, S-U  
Stowage category E

### International Civil Aviation Organization (ICAO-IATA/DGR) - additional information

Danger label(s) 2.1



Special provisions (SP) A1  
Excepted quantities (EQ) E0

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

#### Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)		
Name of substance	Name acc. to inventory	Restriction
isopentane	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC	R3
isopentane	flammable / pyrophoric	R40
ethane	flammable / pyrophoric	R40

## Autogas (nach EN 589)

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

Dangerous substances with restrictions (REACH, Annex XVII)		
Name of substance	Name acc. to inventory	Restriction
propane	flammable / pyrophoric	R40
butane	flammable / pyrophoric	R40
isobutane	flammable / pyrophoric	R40
propene	flammable / pyrophoric	R40
but-1-ene	flammable / pyrophoric	R40

### Legend

R3

- Shall not be used in:
  - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
  - tricks and jokes,
  - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
- Articles not complying with paragraph 1 shall not be placed on the market.
- Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
  - can be used as fuel in decorative oil lamps for supply to the general public, and
  - present an aspiration hazard and are labelled with H304.
- Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
- Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
  - lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";
  - grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';
  - lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.;

R40

- Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:
  - metallic glitter intended mainly for decoration,
  - artificial snow and frost,
  - 'whoopie' cushions,
  - silly string aerosols,
  - imitation excrement,
  - horns for parties,
  - decorative flakes and foams,
  - artificial cobwebs,
  - stink bombs.
- Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:
  - 'For professional users only'.
- By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
- The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

### List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

### Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
P2	flammable gases	10 50	45)

### Notation

45) flammable gases, category 1 or 2

## Autogas (nach EN 589)

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

### VOC Deco-Paint Directive 2004/42/EC

VOC content	100 %
-------------	-------

### Industrial Emissions Directive (IED)

VOC content	100 %
-------------	-------

### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

### Water Framework Directive (WFD)

none of the ingredients are listed

### Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

### National regulations (Austria)

Ordinance on combustible liquids (VbF) not assigned

### National regulations (Germany)

#### Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK 1 slightly hazardous to water  
(water hazard class)

### 15.1.3. Technical instructions on air quality control (Germany)

2

Number	Group of substances	Class	Conc.	Mass flow	Mass concentration	Notation
5.2.5	organic substances		≥ 25 wt%	0,5 kg/h	50 mg/m <sup>3</sup>	3)

Notation

3) a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m<sup>3</sup>, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

### National regulations Switzerland

#### Ordinance on the incentive tax on volatile organic compounds (VOCV)

The product is exempt from the tax. Product is used as motor or thermal fuel.

### National inventories

Country	Inventory	Status
AU	AIIC	not all ingredients are listed
CA	DSL	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed

## Autogas (nach EN 589)

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

Country	Inventory	Status
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
US	TSCA	not all ingredients are listed

### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
EC SI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

### National inventories

All ingredients are listed  
EINECS/ELINCS/NLP (Europe)  
DSL/NDL (Canada)  
ENCS, class 1 and 2 (MITI-inventory, Japan)  
AICS (Australia)  
KECL (Republic of Korea)  
PICCS (Philippines)  
IECSC (China)  
NZIoC (New Zealand)  
REACH (Europe)  
ASIA-PAC (Asia-Pacific Region)  
SWISS (Switzerland)  
Toxic Substance Control Act (TSCA)

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)



## Autogas (nach EN 589)

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

Abbr.	Descriptions of used abbreviations
ADR/RID/ADN	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN)
AGW	Workplace exposure limit
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
COD	Chemical oxygen demand
DFG	Deutsche Forschungsgemeinschaft MAK-und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
GKV	Grenzwerteverordnung
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval

## Autogas (nach EN 589)

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

Abbr.	Descriptions of used abbreviations
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
Press. Gas	Gas under pressure
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
SUVA	Grenzwerte am Arbeitsplatz, Suva
SVHC	Substance of Very High Concern
TRGS	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany)
TRGS 900	Arbeitsplatzgrenzwerte (TRGS 900)
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H220	Extremely flammable gas.
H224	Extremely flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

**Autogas (nach EN 589)**

Version number: 2.0  
Replaces version of: 17.04.2020 (1)

Revision: 09.11.2022

Code	Text
H412	Harmful to aquatic life with long lasting effects.

**Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.